


# Product Specifications

## FlashCheck. Waterproof Lollipop Min/Max Thermometer

<b>Measurement Range</b>	-40°F to 311°F (-40°C to 155°C)
<b>Operating Range</b>	32°F to 122°F (0°C to 50°C)
<b>Accuracy</b>	±1°F (14°F to 194°F), ±0.5°C (-10°C to 90°C) or ±1% whichever is greatest
<b>Sensor</b>	Thermistor
<b>Display Resolution</b>	0.1°F/°C
<b>Display Reading Update</b>	1 second
<b>Display Window Size</b>	1.3 in W x 0.9 in H (32.9 mm W x 22.9 mm H)
<b>Calibration</b>	Auto calibration feature
<b>Battery</b>	Button Cell Alkaline
<b>Body Casing</b>	ABS plastic
<b>Probe Length</b>	4.13 in. (105 mm)
<b>Probe Diameter</b>	0.14 in. (3.56 mm), reduced tip 0.1 in (2.5mm)
<b>Weight</b>	1.3 oz (37.6g)
<b>Waterproof Rating</b>	IP65
<b>Factory Calibration</b>	NIST traceable calibration certified
<b>Compliance Certificate</b>	Manufacturers certificate of compliance available from DeltaTrak, NIST Traceable, NSF, CE



### Model 11050

- NSF certified
- °F/°C selectable
- Min/Max memory stores lowest/highest readings
- Automatic calibration feature
- IP65 Waterproof housing
- Small-diameter probe ideal for measuring temperature of "thin mass" food such as meat patties and chicken/fish fillets (FDA Food Code 4-302.12 (B)).

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system



SS0008 15G1

