

Product Specifications

Min/Max Alarm Digital Thermometer

Temperature Range	Internal Sensor: 14°F to 122°F (-10°C to 50°C) External Sensor: -58°F to 158°F (-50°C to 70°C)
Accuracy	±1.8°F (±1.0°C)
Resolution	0.1°F (0.1°C)
Display Reading Update	10 seconds
Sensor	Thermistor
External Sensor Cable Length	10 ft (3m)
Display Window Size	1.9 in. (W) x .8 in. (H) (48 mm x 21 mm)
Product Size	2.9 in. (W) x 2 in. (H) x 6 in. (D) (73 mm x 52 mm x 15 mm)
Weight	2.5 oz. (70 g)
Body Casing	Polycarbonate and ABS plastic
Probe	Stainless steel probe, .875 in. (L) (17.8 mm)
Battery (included)	1.5 volt AAA/ UM4 or equivalent
Certification / Calibration	CE mark, N.I.S.T. traceable by lot
* Extreme temperatures within the display range cannot be verified for accuracy.	



Model 12207

- High/low temperature alarm setting
- Internal/External sensor switchable
- Display backlight
- °C / °F selectable
- Min/Max memory for internal or external sensor - lowest & highest reading stored for instant recall.
- Memory function holds up to 99 points of temperature data

DeltaTrak manufactures products under an ISO 9000 registered quality management system

SS0013 13K1

